

# Specifications

## bizhub 754e/654e General Specifications

Type	Console Printer / Copier / Scanner	
Copy Resolution	Scan	Main: 600 dpi x Sub: 600 dpi
	Print	1,800 dpi (equivalent) x 600 dpi
Gradation	256	
Memory Capacity (Std./Max.)	2 GB/4 GB	
HDD	250 GB	
Original Type	Sheets, Books, Objects	
Max. Original Size	A3 (11" x 17")	
Output Size	SRA3 to A5, B6S*1, A6S*1 Thick paper, Foolscap*2 (8-1/2" x 13-1/2", 200 mm x 330 mm, 8-1/8" x 13-1/4", 8-1/2" x 13", 8-1/4" x 13", 8" x 13"), 8K, 16K, Long Length Paper (210 x 457.3 mm to 297 x 1,200 mm)	
Image Loss	Max. 4.2 mm or less for top edge (5 mm for thin paper), Max. 3.0 mm or less for bottom edge, Max. 3.0 mm or less for right/left edges *A loss of 4.2 mm each during printing.	
Warm-Up Time (23°C, std. voltage) (May vary depending on the operating environment and usage.)	22 sec. or less (The time required to start printing when both the main power and sub-power switches are turned from OFF to ON.)	
	22 sec. or less (The time required to start printing when the main power switch is ON and the sub-power switch is turned from OFF to ON.)	
First Copy Time*3	754e : 3.6 sec. or less 654e : 3.7 sec. or less	
Copy Speed (A4 Crosswise)	754e : 75 ppm 654e : 65 ppm	
Copy Magnification	Fixed Same Magnification	1:1±0.5% or less
	Scaling Up	1: 1.154/1.224/1.414/2.000
	Scaling Down	1: 0.866/0.816/0.707/0.500
	Preset	3 types
	Zoom	25 to 400% (in 0.1% increments)
	Lengthwise Crosswise Individual Settings	25 to 400% (in 0.1% increments)
Paper Capacity (80 g/m <sup>2</sup> )	Tray 1/2	500 sheets (up to SRA3)
	Tray 3	1,500 sheets (A4)
	Tray 4	1,000 sheets (A4)
	Multiple Bypass Tray	150 sheets (up to SRA3)
Max. Paper Capacity (80 g/m <sup>2</sup> )*4	6,650 sheets	
Paper Weight	Tray 1-4	52 to 256 g/m <sup>2</sup>
	Multiple Bypass Tray	52 to 300 g/m <sup>2</sup>
Multiple Copy	1 to 9,999 sheets	
Auto Duplex	Paper Size	Width: 100 to 320 mm, Length: 148 to 457.2 mm
	Paper Weight	52 to 256 g/m <sup>2</sup>
Power Requirements	AC 230 V 10 A (50 to 60 Hz)	
Max. Power Consumption	2.1 kW or less	
Dimensions [W] x [D] x [H]	650 x 799 x 1,155 mm (25-1/2" x 31-1/2" x 45-1/2")	
Weight	Approx. 201 kg (443-1/4 lb)	
Space Requirements [W] x [D]*5	988 x 1,525 mm (39" x 60")	

\*1 S: Short edge feed

\*2 Set by Customer engineer

\*3 A4 crosswise full size/using the first tray/scanning from the original glass surface.

\*4 With options installed.

\*5 Without options, with paper trays pulled out, and multiple bypass tray, auxiliary tray and ADF opened.

## Printer Specifications

Type	Embedded	
CPU	MPC8536 1.2 GHz	
Memory	Shared with the copier	
Print Speed	Same as Copy Speed (when using the same original)	
HDD	250 GB (Shared with the copier)	
Print Resolution	1,800 dpi (equivalent) x 600 dpi (at smoothing) or 1,200 dpi x 1,200 dpi (in 1,200 dpi mode)*1	
PDL	PCL 5e/c Emulation, PCL 6 Emulation, PostScript (3016) 3 Emulation, XPS (Ver. 1.0)	
Protocol	TCP/IP, IPX/SPX (NDS support), SMB (NetBEUI), LPD, IPP1.1, SNMP, HTTP	
Support OS	Windows Vista / Vista 64bit / 7 / 7 64bit / 8 / 8 64bit / 8.1 / 8.1 64bit Windows Server 2003 / Server 2003 R2 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 Mac OS 9.2 / X 10.2 / X 10.3 / X 10.4 / X 10.5 (PowerPC) / X 10.5 / X 10.6 / X 10.7 / X 10.8 / X 10.9 (Intel), Linux	
Fonts	PCL	80 Roman fonts
	PS	137 Roman Type1 fonts
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T), USB 1.1, USB 2.0, USB Host	

\*1 Output speed will be reduced.

## Scanning Function Specifications

Type	Full-Colour Scanner	
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T)	
Driver	TWAIN Driver, HDD TWAIN Driver	
Protocol	TCP/IP (FTP, SMB, SMTP, WebDAV) (IPv4/IPv6)	
Scanning Speed (Colour/B&W) (400dpi, A4 Crosswise)	Simplex	90 opm
	Duplex	180 opm
Scanning Size	Max. A3 (11" x 17")	
Output Format	TIFF, JPEG, PDF, Compact PDF, XPS, Compact XPS, OOXML (pptx, xlsx*, docx*), Searchable PDF*, PDF/A*, Linearised PDF* *Optional	
Scanning Resolution	Push	200 dpi / 300 dpi / 400 dpi / 600 dpi
	Pull	100 dpi / 200 dpi / 300 dpi / 400 dpi / 600 dpi
Main Functions	Scan to E-Mail, Scan to FTP, Scan to BOX (HDD), Scan to PC (SMB), Network TWAIN, Scan to WebDAV, Scan to Me, Scan to Home, Scan to USB, Scan to Scan Server, Scan to Web Service (WSD-Scan), Device Profile for Web Services (DPWS)	
Other Functions	Multi-Method Send, Authentication at the time of E-Mail send (SMTP authentication, POP before SMTP), S/MIME, Annotation	

## Internet Fax

Protocol	SMTP, POP
Connection Mode	Full-Mode
Sending Paper Size	A3, B4, A4
Recording Paper Size	Max. A3
Resolution	200 x 100 dpi, 200 x 200 dpi, 400 x 400 dpi, 600 x 600 dpi
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T)
Colour	Support Colour Internet Fax
Format	Send: TIFF-F, Receive: TIFF-F Colour/Grey Scale: TIFF (RFC3949 Profile-C)

## Fax Kit FK-511 (Optional)

Communication	Super G3
Compatible Lines	Public Switch Telephone Network, Private Branch Exchange, Fax Communication Line
Line Density	G3 (8 dot/mm x 3.85 line/mm, 600 x 600 dpi)
Modem Speed	2.4 to 33.6 kbps
Compression	MH/MR/MMR/JBIG
Sending Paper Size	Max. A3 (Long Length Support: Max. 1,000 mm)
Recording Paper Size	Max. A3 (Long Length Max. 1,000 mm — following the page division —)
Transmission Speed	Less than 3 sec. (A4, V.34, 33.6 kbps, JBIG)
Memory	Shared with the copier
Number of Abbr. Dials	2,000
Number of Program Dials	400
Number of Group Dials	100
Sequential Multiple Station Transmission	Max. 600

## IP Address Fax (Optional) \*Optional Fax Kit FK-511 is required.

Protocol Transmission	SMTP
Sending Paper Size	A3, B4, A4
Resolution	200 x 200 dpi, 400 x 400 dpi, 600 x 600 dpi
Format	Send: TIFF-F, Receive: TIFF-F Colour/Grey Scale: TIFF (RFC3949 Profile-C)

