

bizhub C35P

full color laser printer



General Specifications:

TYPE:	Full-Color Laser printer with Emperon technology
PRINT PROCESS:	Electrophotographic Laser
PRINT SPEED:	Color: 31 ppm, Monochrome: 31 ppm (letter, portrait)
FIRST-PAGE OUTPUT TIME:	Color: 12.9 seconds, Monochrome: 12.9 seconds
RESOLUTION:	4800 dpi-class x 600 dpi
MAXIMUM MONTHLY DUTY CYCLE:	120,000 prints
STANDARD PAPER INPUT:	100-sheet multipurpose tray, 250-sheet cassette
OPTIONAL PAPER INPUT:	500-sheet lower feeder unit
STANDARD PAPER OUTPUT:	200-sheet face-down output tray
STANDARD AUTOMATIC DUPLEXER:	For two-sided printing (plain paper only)
PAPER SIZE:	100-sheet multipurpose tray: Letter, Legal, 4" x 6", 5.5" x 8.5", A4, A5, A6, B5, B6, Custom sizes: (W) 3.6"-8.5" to (H) 5.8"-14", (W) 92-216 mm to (H) 148-356 mm, Envelopes: Monarch, Com 10, DL, C6 250-sheet cassette: Letter, 4" x 6", 5.5" x 8.5", A4, A5, A6, B5, B6, Custom sizes: (W) 3.6"-8.5" to (H) 5.8"-11.7", (W) 92-216 mm to (H) 148-297 mm 500-sheet lower feeder unit (optional): Letter, Legal, A4, B5 Duplexer: Letter, Legal, A4, B5, Custom sizes: (W) 7.2"-8.5" to (H) 10"-14", (W) 182-216 mm to (H) 254-356 mm
PRINTABLE AREA:	0.165" (4.2 mm) from all edges, 13.7" maximum print length
PAPER WEIGHTS:	Plain Paper: 16-24 lb. Bond (60-90 gsm), Thick Stock: Up to 110 lb. Index (210 gsm)(via multipurpose tray, 250-sheet cassette and duplexer only), Duplexer: Up to 110 lb. Index (60-210 gsm)
PRINT MEDIA:	Plain Paper, Recycled Paper, Letterhead, Thick Stock, Glossy Stock, Laser Quality Labels, Envelopes, Postcards
CONSUMABLES*:	In-Box Toner: Cyan, Magenta, Yellow, Black (Black yield up to 5,200 pages @ 5% coverage / Cyan, Magenta, Yellow yield up to 4,500 pages @ 5% coverage) Replacement Toner: Cyan, Magenta, Yellow, Black (Black yield up to 5,200 pages @ 5% coverage / Cyan, Magenta, Yellow yield up to 4,500 pages @ 5% coverage) Imaging Unit: Cyan, Magenta, Yellow, Black (yield up to 30,000 pages); Waste Toner Box
DIMENSIONS (W x D x H):	16.5" x 20.6" x 13" (419 x 523 x 330 mm)
WEIGHT:	Main body: 49.1 lbs. (22.3 kg); With consumables: 59 lbs. (26.8 kg); With packaging: 67.8 lbs. (30.8 kg)
POWER REQUIREMENTS:	120 VAC (for U.S.), 60 Hz, 220-240 VAC (for Latin America), 50/60 Hz
POWER CONSUMPTION:	Operating: 1100 W or less, Energy Save Mode: 34 W or less, TEC: 6 kWh or less
TEMPERATURE REQUIREMENTS:	Operating: 50° to 86° F (10° to 30° C), Non-Operating: 32° to 95° F (0° to 35° C)
HUMIDITY:	Operating: 15% to 85% RH, Non-Operating: 30% to 85% RH
NOISE LEVELS:	Operating: <54 dB(A), Standby: <39 dB(A)
REGULATORY/SAFETY CONFORMITY:	UL, cUL, CDRH, FCC 15
COLOR CONTROL:	Enhanced Automatic Image Density Control (eAIDC), ICC device profiles, Automatic ICC-based color matching, SWOP, Commercial, Euroscale, DIC, and TOYO press emulations
PROCESSOR:	MV78100 800 MHz
MEMORY (STD./MAX.):	768 MB/768 MB
HARD DISK DRIVE (OPTIONAL):	40 GB (for downloaded fonts, forms and color profiles; electronic collation; job accounting; direct XPS, PDF, JPEG and TIFF printing; proof then print, secured job, print and hold, and stored job functions)
OPERATING SYSTEM COMPATIBILITY:	Windows 7 (x32, x64), Windows Vista (x32, x64), Windows Server 2003 (x32, x64), Windows XP (x32, x64), Windows 2000 (x32, x64), Mac OS X (10.2.8+, 10.3.9+, 10.4, 10.5, 10.6), SuSE Linux Enterprise Desktop 10, Red Hat Enterprise Linux 5 Desktop
INTERFACE SUPPORT:	Gigabit Ethernet (10/100/1000BaseTX), USB 2.0, USB Host Port
PRINTER EMULATIONS:	PostScript 3 (3016), PCL 6 (XL 3.0), XPS 1.0, PDF Direct Print** (v1.7), JPEG/TIFF Direct Print**
TYPEFACES:	137 resident PostScript fonts, 80 PCL fonts
ETHERNET PROTOCOLS:	Bonjour, BOOTP, DHCP, DPWS (WSD), DHCPv6, Dynamic DNS, EtherTalk, FTP, HTTP, HTTPS, IEEE 802.1x, IPv6, IPP1.1, IPP over SSL, IPsec (IPv6), IPX/SPX Netware 4/5/6, LLTD, NTP, SLP, SSL/TLS, SNMP, SNTP, TCP/IP
PRINTER MANAGEMENT:	Download Manager, PageScope Account Manager, PageScope Data Administrator, PageScope Direct Print, PageScope EMS Plug-Ins (Tivoli Netview, CA Unicenter, HP Open View, Microsoft Management Console), PageScope Enterprise Suite Plug-in, PageScope Net Care Device Manager, PageScope Web Connection, Status Monitor
WARRANTY:	1-year

*The stated life expectancy of each consumable is based on printing under specific operating conditions such as page coverage for a particular page size (5% coverage of letter/A4). The actual consumable's life will vary depending on the use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature, and humidity.

**Requires optional Hard Drive



Konica Minolta Optimized Print Services offers a full suite of device output services and workflow solutions that increase efficiency and control costs. Please contact your authorized Konica Minolta sales representative for details.

KONICA MINOLTA
BUSINESS SOLUTIONS U.S.A., INC.
100 Williams Drive
Ramsey, NJ 07446
www.CountOnKonicaMinolta.us
www.kmbs.konicaminolta.us

© 2013 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, Count on Konica Minolta, bizhub and PageScope are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. Design & specifications are subject to change without notice. Some functions may require options, which may or may not be available at time of launch.



Item #: C35PSS
12/4/13