

Specifications		CLX-9201NA	CLX-9251NA	CLX-9301NA
Print				
Engine Speed	Simplex	Mono and Color: Up to 20 ppm in A4/Letter	Mono and Color: Up to 25 ppm in A4/Letter	Mono and Color: Up to 30 ppm in A4/Letter
First Page Out Time (Color and B&W)	From Ready	12 sec. (Color)/10 sec. (Mono)	11.5 sec. (Color)/9.5 sec. (Mono)	11 sec. (Color)/9.5 sec. (Mono)
Resolution	Optical	600 x 600 dpi		
Resolution	Enhanced	Normal: 2400 x 600 dpi Effective Output (600 x 600 x 2 bit), Best: 9600 x 600 dpi Effective Output (600 x 600 x 4 bit), High Quality: Real 1200 x 1200 dpi		
Printer Languages		PCL5C, PCL6 (XL), PostScript Level3, PDF 1.7+, XPS		
Fonts/Downloadable Fonts		PCL: 93 scalable, 1 bitmap, OCR-A,OCR-B, PS:136 / Yes (PCL & PS3 S/W Font)		
Controller and Software				
Processor (CPU)		Chorus4N Dual Core 1GHz		
DRAM	Standard/Max	1GB DDR3 SDRAM		
Storage		320GB HDD Standard (Usable Space [Document Box Space]: 88GB)		
Printer Driver	(Supporting OS)	Windows: 2000/XP (32/64bit)/2003 (32/64bit)/Vista (32/64bit)/2008/Win7/2008 R2 (64 only), Linux: RedHat Enterprise Linux WS 4, 5 (32/64bit)/Fedora 5, 6, 7, 8, 9, 10, 11, 12, 13 (32/64bit)/SuSE Linux 10.1 (32bit) OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64bit)/Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64bit)/Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04 8.10, 9.04, 9.10, 10.04 (32/64bit)/SuSE Linux Enterprise Desktop 10, 11 (32/64bit) Debian 4.0, 5.0 (32/64bit), Mac: OS X 10.5 – 10.7		
Interface				
USB	Host	High-Speed USB 2.0 Host (2-port)		
USB	Device	High-Speed USB 2.0 Peripheral (1-port)		
Wired LAN		Ethernet 10/100/1000 Base TX		
Foreign Device Interface		Optional (CLX-KIT10F)		
Network Interface				
Windows / Mac / Linux / Novell / Others		Microsoft Windows 2000, XP (32/64bit), 2003 (32/64bit), Vista (32/64bit), Win8 / OS 10.5 – 10.7 / RedHat 8 – 9, Fedora Core 1–4, Mandrake 9.2 – 10.1, SuSE 8.2 – 9.2, Netware 5.x (TCP/IP Only), Unix (HP-UX, Solaris, SunOS, SCO)		
NW Protocols	TCP/IP	TCP/IPv4, HTTP, SNMPv1/v2c/v3, LDAP, SMTP, SSL/TLS, IPsec, DNS, WINS, SLP, Bonjour, SDDP, DDNS, DHCP/BOOTP, IPv6		
	NetBIOS over TCP/IP	Yes		
	Others	HTTPS, LDAPS, IPsec		
	IP Addressing	Static IP, Auto IP, BOOTP, DHCP		
User Interface				
Display	LCD	7" 800 x 480 WVGA TFT Color Graphic LCD with Touch-Screen, 24-bit color		
Key/Button		Power, Start, Stop, Interrupt, Numeric Keypad, Reset, Counter, Job Status, Eco, Logout, Clear, On Hook Dial, Redial/Pause		
Scan	Scan Method	Color CCDM-MMT		
	Compatibility	TWAIN (N/W)		
	Resolution	Optical: 600 x 600 ppi, Enhanced: 4,800 x 4,800 ppi		
	Half-tone	256 levels		
	Zoom Range	25% – 400% in 1% increments (Platen/DADF)		
	Multi Copy	1–9999		
Scan-to	HDD	Yes (Shared Folder)		
	USB	Yes		
	Email	Yes		
	Client (NetScan)	Yes (N/W)		
	SMB	Yes		
	FTP	Yes		
	Fax	Compatibility	ITU-T G3, Super G3	
Modem Speed		33.6 Kbps		
Compression		MH/MR/MMR/JBIG		
S. Fine (Super Fine)		300 x 300 dpi		
Speed Dial		500 locations		
Group Dial		Max. 500 Groups (Max. locations per 1 Group: 100 locations)		
Multi-Send		Up to 505 locations		
Paper Handling		Standard Capacity	1,140 sheets, 520-sheet cassette tray x 2, 100-sheet MP tray	
	Max. Input Capacity	MP + 4 Tray: 2,180 sheets		
Multi-Purpose Tray				
Capacity		Plain Paper: 100 sheets @ 80 gsm, Envelopes: 10 sheets @ 75 gsm, Labels: 20 sheets @ 120 – 159 gsm, Thick Paper: 10 sheets @ 176 gsm		
Media Sizes		98 x 148 mm – 297 x 432 mm (3.87 x 5.8" – 11.7 x 17")		
Media Type		Printer Default, Plain, Thick, Thin, Bond, Color, Cardstock, Labels, Envelope, Preprinted, Letterhead, Recycled, Cotton, Archive, Glossy		
Media Weight		16 – 46 lb. (60 to 175): Simplex, Duplex		
Sensing		H/W Install Detect, Paper Empty and Low Level Detect, Paper Size Detect		
Standard Cassette Tray				
Capacity		520 sheets @ 20 lb. (80 g/m ²) x 2		
Media Sizes		Ledger, A3, Letter, Legal, Oficio, Folio, A3, A4, JIS B5, ISO B5, Executive, A5, Statement, Custom		
Media Type		Plain, Thin, Bond, Punched, Pre-Printed, Recycled, Label, Cardstock, Letterhead, Thick, Cotton, Colored, Archive, Glossy		
Media Weight		16 lb. Bond to 120 lb. Index		
Dual Cassette Feeder				
Capacity		520 sheets @ 20 lb. (80 g/m ²) x 2		
Media Sizes		Ledger, A3, Letter, Legal, Oficio, Folio, A4, JIS B5, ISO B5, Executive, A5, Statement, Custom		
Media Type		Plain, Thin, Bond, Punched, Pre-Printed, Recycled, Label, Cardstock, Letterhead, Thick, Cotton, Colored, Archive, Glossy		
Media Weight		16 lb. Bond to 120 lb. Index		
Automatic Duplex				
Supporting				
DADF				
Capacity		100 sheets (21 lb., 80 g/m ²)		
Document Size		Width: 140 – 297mm, Length: 140 – 432mm		
Consumables				
CRU		Yellow Toner: CLT-Y809S, Magenta Toner: CLT-M809S, Cyan Toner: CLT-C809S, Black Toner: CLT-K809S, Imaging Unit Kit: CLT-R809, Waste Toner Box: CLT-W809		
Toner (Polymerized)	Black / Color	20,000 impressions @ 5% Mono Chart / 15,000 impressions @ 5% Color Chart		
Environment				
		AC 110 – 127V (-10%–6%)		
Dimensions		22.05" (W) x 24" (D) x 33.24" (H) (Includes Standard Document Feeder)		
Weight		160 lbs. (With Standard Document Feeder)		
Options				
Dual Cassette Feeder / Inner Finisher		CLX-PPF100 / CLX-FIN50S (50-Sheet Inner Finisher)		
Job Separator Tray / Fax Kit / Cabinet Stand / FDI Kit / Working Table / Staples		SCX-CLX-JST100 (Job Separator) / SCX-CLX-FAX160 / CLX-DSK20T / CLX-KIT10F / CLX-WKT001 / SCX-STP000		

Product Support: 1-866-SAM4BIZ | 1-800-SAMSUNG | samsung.com/printer

Follow us:  @SamsungBizUSA |  youtube.com/samsungbizusa



©2013 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and designs are subject to change without notice. Print speed will be affected by operating system used, computing performance, application software, connection method, media type, media size and job complexity. Copy speed is based on Single Document Multiple Copy. Non-metric weights and measurements are approximate. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Simulated screen images. See samsung.com for detailed information. Printed in USA on 50% recycled (30% post-consumer waste) paper using soy inks. PNT-CLX9201 NACLX9301NA-MAY13T

