


Specifications

bizhub C368/C308/C258 General Specifications

		bizhub C368	bizhub C308	bizhub C258
Type	Desktop Full Colour Printer / Copier / Scanner			
Colour Support	Full colour			
Copy Resolution	Scan	Main: 600 dpi × Sub: 600 dpi		
	Print	1,800 dpi (equivalent) × 600 dpi		
Gradation	256			
Memory Capacity (Std./Max.)	2 GB/4 GB			
HDD	250 GB			
Original Type	Sheets, Books, Objects			
Max. Original Size	A3 (11" × 17")			
Output Size	Main unit: SRA3*, A3 to A5, 12-1/4" × 18" (A3 wide (311.1 mm × 457.2 mm)), 11" × 17" to 8-1/2" × 11", 5-1/2" × 8-1/2", 8" × 13", 16K, 8K Bypass Tray: SRA3, A3 to A5, B6*, A6*, 12" × 18" (A3 wide (311.1 mm × 457.2 mm)), 11" × 17" to 5-1/2" × 8-1/2", 8" × 13", 16K, 8K, Postcard (A6 (4" × 6" Card)), Envelope*, Label sheet, Tab paper, Banner paper (Width: 210 mm to 297 mm (8-1/4" to 11-11/16")), Length: 457 mm to 1,200 mm (18" to 47-1/4")*			
Image Loss	Max. 4.2mm or less for top edge (5 mm for thin paper), Max. 3.0mm or less for bottom edge, Max. 3.0mm or less for right/left edges *A loss of 4.2 mm each during printing.			
Warm-Up Time*7 (23°C, std. voltage)	Colour/B&W: 20 sec. or less			
* The time required to start printing when both the main power and sub-power switches are turned from OFF to ON.				
* The time required to start printing when the main power switch is ON and the sub-power switch is turned from OFF to ON.				
First Copy Out Time*8	Colour	6.9 sec. or less	7.3 sec. or less	7.5 sec. or less
	B&W	5.3 sec. or less	5.6 sec. or less	6.1 sec. or less
Copy Speed (Colour/B&W, A4)	36 ppm		30 ppm	25 ppm
Copy Magnification	Fixed Same Magnification	1: 1±0.5% or less		
	Scaling Up	1: 1.154/1.224/1.414/2.000		
	Scaling Down	1: 0.866/0.816/0.707/0.500		
	Preset	3 types		
	Zoom	25 to 400% (in 0.1% increments)		
	Lengthwise Crosswise Individual Settings	25 to 400% (in 0.1% increments)		
Paper Capacity (80 g/m ²)	Tray 1	500 sheets (up to A3)		
	Tray 2	500 sheets (up to SRA3)		
	Multiple Bypass Tray	150 sheets (up to SRA3)		
Max. Paper Capacity (80 g/m ²)*9	6,650 sheets			
Paper Weight	Tray 1 / 2	52 to 256 g/m ²		
	Multiple Bypass Tray	60 to 300 g/m ²		
Multiple Copy	1 to 9,999 sheets			
Auto Duplex	Paper Size	SRA3, A3 to A5, B6*, A6*, 12-1/4" × 18" (A3 wide (311.1 mm × 457.2 mm)), 11" × 17" to 5-1/2" × 8-1/2", 7-1/4" × 10-1/2", 8" × 13", 16K, 8K, Postcard (A6 (4" × 6" Card))		
	Paper Weight	52 to 256 g/m ²		
Power Requirements	AC220 to 240 V 8.0 A (50/60 Hz)			
Max. Power Consumption	1.5 kW or less			
Dimensions [W] × [D] × [H]	615 × 695 × 779 mm (24-3/16" × 27-15/16" × 30-11/16")			
Weight	Approx. 85 kg (187-3/8 lb)			
Space Requirements [W] × [D]*10	937 × 1,214 mm (36-7/8" × 47-13/16")			

- *1 SRA3 paper can be used in Tray2.
 *2 There are four types of foolscap: 8-1/2" × 13-1/2", 8-1/2" × 13", 8-1/4" × 13", and 8" × 13". Any one of these sizes is selectable. For details, contact your service representative.
 *3 Short edge feed 
 *4 There are six types of foolscap: 8-1/2" × 13-1/2", 220 mm × 330 mm², 8-1/2" × 13", 8-1/4" × 13", 8-1/8" × 13-1/4", and 8" × 13". Any one of these sizes is selectable. For details, contact your service representative.
 *5 Wrinkles or printing errors may occur due to the type, storage or environment that exists when envelope printing is carried out.
 *6 Printing on banner paper can only be performed from a PC.
 *7 May vary depending on the operating environment and usage.
 *8 A4 long edge feed full size/using the first tray/scanning from the original glass surface.
 *9 With options installed.
 *10 Without options, with paper trays pulled out, and multiple bypass tray, auxiliary tray and ADF opened.

Printer Specifications

Type	Embedded	
CPU	ARM Cortex-A7 Dual-core 1.2GHz	
Memory	Shared with the copier	
Print Speed	Same as Copy Speed (when using the same original)	
HDD	250 GB (Shared with the copier)	
Print Resolution	1,800 dpi (equivalent) × 600 dpi (at smoothing) or 1,200 dpi × 1,200 dpi (in 1,200 dpi mode)	
PDL	PCL 6, PostScript 3 Emulation, XPS	
Protocol	TCP/IP, IPX/SPX (NDS support), SMB (NetBEUI), LPD, IPP1.1, SNMP, AppleTalk	
Support OS	Windows Vista*1 / 7*1 / 8*1 / 8.1*1 / 10*1	
	Windows Server 2008*1 / 2008 R2 / 2012 / 2012 R2 Mac OS X (10.6 / 10.7 / 10.8 / 10.9 / 10.10 / 10.11) Linux	
Fonts	PCL	80 Roman fonts
	PS	137 Roman Type1 fonts
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T), USB 1.1, USB 2.0, IEEE 802.11 b/g/n*2	

- *1 Supports the 32-bit (x86) or 64-bit (x64) environment.
 *2 Optional

Scanning Specifications

Type	Full-Colour Scanner	
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T), IEEE 802.11 b/g/n*1	
Driver	TWAIN Driver, HDD TWAIN Driver	
Protocol	TCP/IP (FTP, SMB, SMTP, WebDAV) (IPv4/IPv6)	
Scanning Speed (Colour/B&W) (300 dpi, A4, Simplex)	80 opm**	
Scanning Size	Max. A3 (11" × 17")	
Output Format	TIFF, JPEG, PDF, Compact PDF, XPS, Compact XPS, OOXML (pptx, xlsx*, docx*), Searchable PDF*, PDF/A*, Linearised PDF**	
Scanning Resolution	Push	200 dpi / 300 dpi / 400 dpi / 600 dpi
	Pull	100 dpi / 200 dpi / 300 dpi / 400 dpi / 600 dpi
Main Functions	Scan to E-Mail, Scan to FTP Scan to BOX (HDD), Scan to PC (SMB), Network TWAIN, Scan to WebDAV, Scan to USB, Scan to Scan Server, Scan to Web Service (WSD-Scan), Device Profile for Web Services (DPWS)	
Other Functions	Multi-Method Send, Authentication at the time of E-Mail send (SMTP authentication, POP before SMTP), S/MIME, Annotation	

Internet Fax

Protocol	TX: SMTP, RX: POP3, TCP/IP Simple mode	
Connection Mode	Full-Mode	
Sending Paper Size	A3, B4, A4	
Recording Paper Size	Max. A3	
Resolution	B/W: 200 × 100 dpi, 200 × 200 dpi, 400 × 400 dpi, 600 × 600 dpi Colour: 200 × 200 dpi, 400 × 400 dpi, 600 × 600 dpi	
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T)	
Colour	Support Colour Internet Fax	
Format	B/W: TIFF-F Colour: TIFF (Conforms to RFC3949 Profile-C)	

Fax Kit FK-514 (Optional)

Communication	Super G3	
Compatible Lines	Public Switch Telephone Network, Private Branch Exchange, Fax Communication Line	
Line Density	Ultra Fine: 600 dpi 600 dpi	
	Super Fine: 18 dot/mm 15.4 line/mm, 400 dpi 400 dpi	
	Fine: 8 dot/mm 7.7 line/mm, 200 dpi 200 dpi Normal: 8 dot/mm 3.85 line/mm	
Modem Speed	2.4 to 33.6 kbps	
Compression	MH/MR/MMR/JBIG	
Sending Paper Size	Max. A3 (Long Length Support: Max. 1,000 mm)	
Recording Paper Size	Max. A3 (Long Length Max. 1,000 mm — following the page division —)	
Transmission Speed	Less than 2 sec. (A4, V.34, 33.6 kbps, JBIG)	
Memory	Shared with the copier	
Number of Abbr. Dials	2,000	
Number of Program Dials	400	
Number of Group Dials	100	
Sequential Multiple Station Transmission	Max. 600	

IP Address Fax *Optional Fax Kit FK-514 is required.

Protocol/Transmission	TCP/IP, SMTP	
Sending Paper Size	A3, B4, A4	
Resolution	200 × 200 dpi, 400 × 400 dpi, 600 × 600 dpi	
Format	B/W: TIFF-F, TIFFS Colour: TIFF, PDF	

Fiery Image Controller IC-416 (Optional)

* Optional Upgrade Kit UK-211 and Video Interface Kit VI-508 is required.

Type	Embedded	
CPU	Intel Pentium G850 2.9GHz	
Memory	2 GB	
HDD	500 GB	
Print Speed	Same as Copy Speed (when using the same original)	
Print Resolution	1,800 dpi (equivalent) × 600 dpi (at smoothing) or 1,200 dpi × 1,200 dpi (in 1,200 dpi mode)	
PDL	Adobe PostScript 3	
Protocol	Ethernet (Apple Talk, TCP/IP), HTTP/HTTPS, SSL/TLS for HTTPS, SNMP v3, SMB, Port9100 (Bi-Directional), IPP, LDAP, IPv6	
Support OS	Windows Vista*1 / 7*1 / 8*1 / 8.1*1 / 10*1	
	Windows Server 2008*1 / 2008 R2 / 2012 / 2012 R2	
	Mac OS X (10.6 / 10.7 / 10.8 / 10.9 / 10.10 / 10.11)	
Fonts	Adobe PS 138 Roman fonts, Agfa PCL 80 Roman fonts and 1 bitmap font, Additional PCL 35 fonts, Euro Currency Resident Font	
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T)	

*1 Supports the 32-bit (x86) or 64-bit (x64) environment.

Reverse Automatic Document Feeder DF-629 (Optional)

Type	Circulatory duplex system	
Support Paper Size	Max. A3 (Fax mode: Max. 1,000 mm)	
Mixed Size	Support	
Original Set	Centre guide	
Support Paper Weight	Thin paper: 35 to 49 g/m ² (Simplex) Plain paper: 50 to 128 g/m ² (Duplex/Mixed Original)	
Paper Capacity	Max. 100 sheets (80 g/m ²)	
Productivity (A4)	Simplex	Colour/B&W: 80 opm (300 dpi), 55 opm (600 dpi)
	Duplex	Colour/B&W: 37 opm (300 dpi), 26 opm (600 dpi)
Power Requirements	Supplied from the MFP main body	
Dimensions [W] × [D] × [H]	611 × 504 × 127 mm (24-1/16" × 19-13/16" × 5")	
Weight	Approx. 9 kg (19-13/16 lb)	



Dual Scan Document Feeder DF-704 (Optional)

Type	Single pass simultaneous duplex system	
Support Paper Size	Max. A3 (Fax mode: Max. 1,000 mm)	
Mixed Size	Support	
Original Set	Centre guide	
Support Paper Weight	Thin paper: 35 to 49 g/m ² (Simplex) Plain paper: 50 to 163 g/m ² (Simplex/Duplex), 50 to 128 g/m ² (Mixed Original)	
Paper Capacity	Max. 100 sheets (80 g/m ²)	
Productivity (A4)	Simplex	Colour/B&W: 80 opm (300 dpi), 55 opm (600 dpi)
	Duplex	Colour/B&W: 110 opm (300 dpi), 110 opm (600 dpi)
Power Requirements	Supplied from the MFP main body	
Dimensions [W] × [D] × [H]	611 × 504 × 142 mm (24-1/16" × 19-13/16" × 5-9/16")	

