

Specifications	K4350LX	K4300LX	K4250LX
<b>Print</b>			
Speed	Up to 35 ppm in A4/Letter (Up to 19 ppm in A3)	Up to 30 ppm in A4/Letter (Up to 16 ppm in A3)	Up to 25 ppm in A4/Letter (Up to 14 ppm in A3)
First Print Out Time	Less than 7.5 sec	Less than 8.0 sec	Less than 8.5 sec
Resolution/Enhanced	600 x 600 dpi / Up to 1200 x 1200 dpi with Reduced Speed		
Emulation	PCL5e / PCL6 / PostScript3 / PDF V1.7		
Duplex	Up to 23 ipm in A4/Letter Up to 35 ipm in Letter with 2nd Exit (Up to 12 ipm in A3)	Up to 20 ipm in A4/Letter Up to 30 ipm in Letter with 2nd Exit (Up to 11 ipm in A3)	Up to 19 ipm in A4/Letter Up to 25 ipm in Letter with 2nd Exit (Up to 9 ipm in A3)
<b>Copy</b>			
Speed	Up to 35 cpm in A4/Letter	Up to 30 cpm in A4/Letter	Up to 25 cpm in A4/Letter
First Copy Out Time	Less than 4.9 sec	Less than 5.5 seconds	Less than 6.2 seconds
Resolution (Platen / DADF)	Scan: 600 x 600 dpi / Printing: 600 x 600 dpi		
Reduce & Enlarge	25% ~ 400% (Platen Copy), 25% ~ 200% (Single pass duplexing ADF Copy)		
Multi Copy	1 - 9,999		
Duplex Copy	Built-in		
Copy Features	ID Copy / N-up / Booklet / Image Repeat / Auto Fit / Book Copy / Poster Copy / Watermark / Image Overlay / Stamp / Covers / Job Build / Preview / Erase Edge / Image Shift / Image Adjustment / Background Adjustment		
<b>Scan</b>			
Compatibility	Network TWAIN / Network SANE		
Method	MMT		
Resolution (Optical / Enhanced)	Up to 600 x 600 dpi / Up to 4,800 x 4,800 dpi		
Scan to / Destination	Scan to: TIFF-S / TIFF-M / JPEG / PDF / Compact PDF / XPS / Destination: EMAIL / FTP / SMB / HDD / USB / WSD / PC		
<b>Fax</b>			
Compatibility	ITU-T G3 / Super G3		
Modem Speed	33.6 Kbps		
Resolution (Mono)	Up to 600 x 600 dpi		
Fax Feature	On hook Dial, Search, Speed Dial, TAD I/F, Tone/Pulse, Pause, Auto Redial, Last Number Redial, Caller ID, External Phone Interface, Fax Forward to E-Mail, Broadcasting, Delayed Fax		
<b>Paper Handling</b>			
Input Capacity and Types	Standard: 1,140-sheet cassette Tray, 100-sheet MP tray / Max: 2,180 sheets		
Output Capacity and Type	500 sheets Face Down		
Standard Cassette	Media Sizes	Cassette 1: 148.5 x 210 mm ~ 297 x 354 mm (5.8" x 8.2" ~ 11.7" x 14") / Cassette 2: 148.5 x 210 mm ~ 297 x 432 mm (5.8" x 8.2" ~ 11.7" x 17")	
	Media Types	Plain / Thin / Bond / Hole Punched / Pre-Printed / Recycled / Thin CardStock / Letterhead / Thick / Cotton / Colored / Archive / Thin Glossy / Heavy Weight / Extra Heavy Weight	
Multipurpose Tray	Media Sizes	98 x 148 mm ~ 297 x 432 mm (3.8" x 5.8" ~ 11.7" x 17")	
	Media Types	Plain / Thin / Bond / Hole Punched / Pre-Printed / Recycled / Thin CardStock / Letterhead / Thick / Cotton / Colored / Archive / Thin Glossy / Heavy Weight / Envelope / Label	
ADF Document Size	Width: 5" - 11.7" (128 - 297 mm) / Length: 5.5" - 17" (140 - 432 mm)		
Capacity	100-Sheet Single Pass Duplexing ADF		
<b>General Features</b>			
Mobility	Google Cloud Print, Apple AirPrint, Samsung Mobile Print, NFC Tap and Print (optional)		
Display	10.1" Color Touch-Panel LCD (960 x 600)		
Interface	Hi-Speed USB 2.0 Host, Std Ethernet 10/100/1G Base TX (Wired LAN), IEEE 802.11b/g/n + NFC Active Type (Optional)		
Noise Level	Less than 51 dBA (Sound Pressure) / Standby: Less than 30 dBA (Sound Pressure) / Sleep: less than 27 dBA (Sound Pressure)	Printing: Less than 51 dBA (Sound Pressure) / Standby: Less than 30 dBA (Sound Pressure) / Sleep: Less than 27 dBA (Sound Pressure)	Printing: Less than 50 dBA (Sound Pressure) / Standby: Less than 30 dBA (Sound Pressure) / Sleep: Less than 27 dBA (Sound Pressure)
Memory	2 GB		
HDD Standard	320 GB		
OS Compatibility	- Windows: XP (32 / 64 bit) / Vista (32 / 64 bit) / 2003 Server (32 / 64 bit) / 2008 Server (32 / 64 bit) / Win7 (32 / 64 bit) / 2008 R2 (64 bit) / Win8 (32 bit / 64 bit) - Linux: RedHat Enterprise Linux WS 4 / 5 / 6 (32 / 64 bit) / Fedora 5 - 15 (32 / 64 bit) / openSUSE 10.2, 10.3, 11.0, 11.1, 11.2, 11.3, 11.4 (32 / 64 bit) / Mandriva 2007, 2008, 2009, 2009.1, 2010 (32 / 64 bit) / Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10, 10.04, 10.10, 11.04 (32 / 64 bit) / SUSE Linux Enterprise Desktop 10, 11 (32 / 64 bit) / Debian 4.0, 5.0, 6.0 (32 / 64 bit) - UNIX: Sun Solaris 9, 10, 11 (x86, SPARC) / HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) / IBM AIX 5.1, 5.2, 5.3, 5.4, 6.1, 7.1 (PowerPC) - Mac OS: X 10.5 - 10.9		
Monthly Duty Cycle	85,000 sheets/month	76,000 sheets/month	65,000 sheets/month
Dimension (W x D x H)	22.3" x 24" x 32.6"		
Weight	150.2 lbs. with Consumables	150.2 lbs. with Consumables	145.93 lbs. with Consumables
<b>Consumables</b>			
MLT-D708S - Black Toner	25,000 Pages*		
MLT-D708L - Black Toner, High Yield	35,000 Pages*		
MLT-R708 - Imaging Unit	200,000 Pages*		
MLT-W708 - Waste Container	100,000 Pages		

\*Declared cartridge yield in accordance with ISO/IEC 19752

# SAMSUNG

For complete product information and accessories, visit [samsung.com/business](http://samsung.com/business) or [samsung.com/b2bprinters](http://samsung.com/b2bprinters)

Product Support: 1-800-SAMSUNG or 1-866-SAM4BIZ | Follow Us:  [youtube.com/samsungbizusa](http://youtube.com/samsungbizusa) |  [@SamsungBizUSA](https://twitter.com/SamsungBizUSA)



Samsung Electronics has been named 2013 ENERGY STAR Partner of the Year in the product manufacturing category by the U.S. Environmental Protection Agency (EPA).

©2015 Samsung Electronics America, Inc. Samsung is a registered trademark of Samsung Electronics Corp., Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. Intel, the Intel logo, Intel Core and Core Inside are all trademarks of Intel Corporation in the U.S. and other countries. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. See [samsung.com](http://samsung.com) for detailed information. Printed in USA on 50% recycled (30% post-consumer waste) paper using soy inks. PNT-K4350LXK4300LXK4250LXBRO-JAN15T

