


# Specifications

## bizhub C364e/C284e/C224e General Specifications

	bizhub C364e	bizhub C284e	bizhub C224e
Type	Desktop Full Colour Printer / Copier / Scanner		
Colour Support	Full colour		
Copy Resolution	Main: 600 dpi × Sub: 600 dpi		
	Print: 1,800 dpi (equivalent) × 600 dpi		
Gradation	256		
Memory Capacity (Std./Max.)	2 GB/4 GB		
HDD	250 GB		
Original Type	Sheets, Books, Objects		
Max. Original Size	A3 (11" × 17")		
Output Size	SRA3 to A5, B6S*, A6S*, Thick paper, Foolscap** (8-1/2" × 13-1/2", 200 mm × 330 mm, 8-1/8" × 13-1/4", 8-1/2" × 13", 8-1/4" × 13", 8" × 13", 8K, 16K, Long Length Paper (210 × 457.3 mm to 297 × 1,200 mm))		
Image Loss	Max. 4.2mm or less for top edge (5 mm for thin paper), Max. 3.0mm or less for bottom edge, Max. 3.0mm or less for right/left edges *A loss of 4.2 mm each during printing.		
	Colour/B&W: 20 sec. or less	Colour/B&W: 20 sec. or less	Colour/B&W: 20 sec. or less
Warm-Up Time*3 (23°C, std. voltage) *The time required to start printing when both the main power and sub-power switches are turned from OFF to ON. *The time required to start printing when the main power switch is ON and the sub-power switch is turned from OFF to ON.	Colour/B&W: 20 sec. or less	Colour/B&W: 20 sec. or less	Colour/B&W: 18 sec. or less
	Colour: 6.9 sec. or less B&W: 5.3 sec. or less	Colour: 7.7 sec. or less B&W: 5.9 sec. or less	Colour: 8.3 sec. or less B&W: 6.9 sec. or less
First Copy Out Time**4	Colour: 6.9 sec. or less B&W: 5.3 sec. or less	Colour: 7.7 sec. or less B&W: 5.9 sec. or less	Colour: 8.3 sec. or less B&W: 6.9 sec. or less
Copy Speed (A4 Crosswise)	Colour/B&W: 36 ppm	Colour/B&W: 28 ppm	Colour/B&W: 22 ppm
Copy Magnification	Fixed Same Magnification	1: 1±0.5% or less	
	Scaling Up	1: 1.154/1.224/1.414/2.000	
	Scaling Down	1: 0.866/0.816/0.707/0.500	
	Preset	3 types	
	Zoom	25 to 400% (in 0.1% increments)	
	Lengthwise Crosswise Individual Settings	25 to 400% (in 0.1% increments)	
Paper Capacity (80 g/m <sup>2</sup> )	Tray 1	500 sheets (up to A3)	
	Tray 2	500 sheets (up to SRA3)	
	Multiple Bypass Tray	150 sheets (up to SRA3)	
Max. Paper Capacity (80 g/m <sup>2</sup> )*5	3,650 sheets		
Paper Weight	Tray 1 / 2	52 to 256 g/m <sup>2</sup>	
	Multiple Bypass Tray	60 to 300 g/m <sup>2</sup>	
Multiple Copy	1 to 9,999 sheets		
Auto Duplex	Paper Size	Width: 100 to 320 mm, Length: 148 to 457.2 mm	
	Paper Weight	52 to 256 g/m <sup>2</sup>	
Power Requirements	AC220 to 240 V 8 A (50 to 60 Hz)		
Max. Power Consumption	1.58 kW or less		
Dimensions [W] × [D] × [H]	615 × 685 × 779 mm (24-1/4" × 27-1/2" × 30-3/4")		
Weight	Approx. 85 kg (187-1/2 lb)		
Space Requirements [W] × [D]**6	937 × 1,214 mm (37" × 47-3/4")		

- \*1 S: Short edge feed 
- \*2 Set by Customer engineer
- \*3 May vary depending on the operating environment and usage.
- \*4 A4 crosswise full size/using the first tray/scanning from the original glass surface.
- \*5 With options installed.
- \*6 Without options, with paper trays pulled out, and multiple bypass tray, auxiliary tray and ADF opened.

## Printer Specifications

Type	Embedded	
CPU	SOC 800 MHz (DualCore)	
Memory	Shared with the copier	
Print Speed	Same as Copy Speed (when using the same original)	
HDD	250 GB (Shared with the copier)	
Print Resolution	1,800 dpi (equivalent) × 600 dpi (at smoothing) or 1,200 dpi × 1,200 dpi (in 1,200 dpi mode)*1	
PDL	PCL 5e/c Emulation, PCL 6 Emulation, PostScript 3 (3016) Emulation, XPS (Ver.1.0)	
Protocol	TCP/IP, IPX/SPX (NDS support), SMB (NetBEUI), LPD, IPP1.1, SNMP, HTTP	
Support OS	Windows Vista / Vista 64bit / 7 / 7 64bit / 8 / 8 64bit / 8.1 / 8.1 64bit / Windows Server 2003 / Server 2003 64bit / Server 2003 R2 / Server 2003 R2 64bit / Server 2008 / Server 2008 64bit / Server 2008 R2 / Server 2012 / Server 2012 R2 / Mac OS 9.2 / X 10.2 / X 10.3 / X 10.4 / X 10.5 / X 10.6 / X 10.7 / X 10.8 / X 10.9 Linux	
Fonts	PCL	80 Roman fonts
	PS	137 Roman Type1 fonts
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T), USB 1.1, USB 2.0, USB Host	

\*1 Output speed will be reduced.

## Scanning Specifications

Type	Full-Colour Scanner	
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T)	
Driver	TWAIN Driver, HDD TWAIN Driver	
Protocol	TCP/IP, FTP, SMB, SMTP, WebDAV (IPv4/IPv6)	
Scanning Speed (Colour/B&W) (800 dpi, A4 Crosswise)	Simplex	80 opm
	Duplex (DF-701)	160 opm
Scanning Size	Max. A3 (11" × 17")	
Output Format	TIFF, JPEG, PDF, Compact PDF, XPS, Compact XPS, OOXML (pptx, xlsx*, docx*), Searchable PDF*, PDF/A*, Linearised PDF** *Optional	
Scanning Resolution	Push	200 dpi / 300 dpi / 400 dpi / 600 dpi
	Pull	100 dpi / 200 dpi / 300 dpi / 400 dpi / 600 dpi
Main Functions	Scan to E-Mail, Scan to FTP Scan to BOX (HDD), Scan to PC (SMB), Network TWAIN, Scan to WebDAV, Scan to Me, Scan to Home, Scan to USB, Scan to Scan Server, Scan to Web Service (WSD-Scan), Device Profile for Web Services (DPWS)	
Other Functions	Multi-Method Send, Authentication at the time of E-Mail send (SMTP authentication, POP before SMTP), S/MIME, Annotation	

## Internet Fax

Protocol	SMTP, POP
Connection Mode	Full-Mode
Sending Paper Size	A3, B4, A4
Recording Paper Size	Max. A3
Resolution	200 × 100 dpi, 200 × 200 dpi, 400 × 400 dpi, 600 × 600 dpi
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T)
Colour	Support Colour Internet Fax

## Fax Kit FK-511 (Optional)

Communication	Super G3
Compatible Lines	Public Switch Telephone Network, Private Branch Exchange, Fax Communication Line
Line Density	G3 (8 dot/mm × 3.85 line/mm, 600 × 600 dpi)
Modem Speed	2.4 to 33.6 kbps
Compression	MH/MR/MMR/JBIG
Sending Paper Size	Max. A3 (Long Length Support: Max. 1,000 mm)
Recording Paper Size	Max. A3 (Long Length Max. 1,000 mm — following the page division —)
Transmission Speed	Less than 3 sec. (A4, V34, 33.6 kbps, JBIG)
Memory	Shared with the copier
Number of Abbr. Dials	2,000
Number of Program Dials	400
Number of Group Dials	100
Sequential Multiple Station Transmission	Max. 600

## IP Address Fax

\*Optional Fax Kit FK-511 is required.

Protocol Transmission	SMTP
Sending Paper Size	A3, B4, A4
Resolution	200 × 200 dpi, 400 × 400 dpi, 600 × 600 dpi
Format	Send: TIFF-F, Receive: TIFF-F Colour/Grey Scale: TIFF (RFC3949 Profile-C)

## Fiery Image Controller IC-414 (Optional)

(For bizhub C364e/C284e Only) \*Optional Video Interface Kit VI-506 is required.

Type	Embedded
CPU	Intel Pentium E5300 2.60 GHz
Memory	2 GB
HDD	160 GB
Print Speed	Same as Copy Speed (when using the same original)
Print Resolution	1,800 dpi (equivalent) × 600 dpi (at smoothing) or 1,200 dpi × 1,200 dpi (in 1,200 dpi mode)*1
PDL	PCL 6, Adobe PostScript 3 (3019)
Protocol	Ethernet (Apple Talk, TCP/IP), HTTP/HTTPS, SSL/TLS for HTTPS, SMB, Port9100 (Bi-Directional), IPP, LDAP, IPv6, SNMP v3
Support OS	Windows Vista / Vista 64bit / 7 / 7 64bit / 8 / 8 64bit / 8.1 / 8.1 64bit / Windows Server 2003 / Windows Server 2003 64bit / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Mac OS X 10.4.11 / X 10.5 / X 10.6 / X 10.7 / X 10.8 / X 10.9
Fonts	Adobe PS 138 Roman fonts, Agfa PCL 80 Roman fonts and 1 bitmap font, Additional PCL 35 fonts, Euro Currency Resident Font
Interface	Ethernet (10BASE-T/100BASE-TX/1000BASE-T), USB

\*1 Output speed will be reduced.

## Dual Scan Document Feeder DF-701 (Optional)

Type	Single pass simultaneous duplex system	
Support Paper Size	A3 to A6S*, 11" × 17" to 5-1/2" × 8-1/2", Foolscap** (8-1/2" × 13-1/2", 200 mm × 330 mm, 8-1/8" × 13-1/4", 8-1/2" × 13", 8-1/4" × 13", or 8" × 13"), 8K, 16K	
Mixed Size	Support	
Original Set	Centre guide	
Resolution	600 dpi support	
Support Paper Weight	Simplex	Simplex: 35 to 163 g/m <sup>2</sup> ; Duplex: 50 to 163 g/m <sup>2</sup>
	Duplex	Mixed Original: 50 to 128 g/m <sup>2</sup> FAX Mode: 35 to 163 g/m <sup>2</sup> (Simplex), 50 to 163 g/m <sup>2</sup> (Duplex)
Paper Capacity	Max. 100 sheets (80 g/m <sup>2</sup> )	
Productivity (A4 Crosswise)	Simplex	Copy (Colour/B&W): 55 opm (600 dpi) Scan (Colour/B&W): 80 opm (300 dpi)
	Duplex	Copy (Colour/B&W): 110 opm (600 dpi) Scan (Colour/B&W): 160 opm (300 dpi)
Power Requirements	Supplied from the MFP main body	
Max. Power Consumption	74.5 W or less	
Dimensions [W] × [D] × [H]	611.2 × 503.6 × 130 mm (24" × 19-3/4" × 5")	
Weight	Approx. 12 kg (26-1/2 lb)	

\*1 S: Short edge feed 

\*2 Set by Customer engineer

## Reverse Automatic Document Feeder DF-624 (Optional)

Type	Circulatory duplex system	
Support Paper Size	A3 to A6S*, 11" × 17" to 5-1/2" × 8-1/2", Foolscap** (8-1/2" × 13-1/2", 200 mm × 330 mm, 8-1/8" × 13-1/4", 8-1/2" × 13", 8-1/4" × 13", or 8" × 13"), 8K, 16K	
Mixed Size	Support	
Original Set	Centre guide	
Resolution	600 dpi support	
Support Paper Weight	Simplex	Simplex: 35 to 128 g/m <sup>2</sup> Duplex/Mixed Original: 50 to 128 g/m <sup>2</sup> FAX Mode: 35 to 128 g/m <sup>2</sup> (Simplex), 50 to 128 g/m <sup>2</sup> (Duplex)
	Duplex	Copy (Colour/B&W): 26 opm (600 dpi) Scan (Colour/B&W): 37 opm (300 dpi)
Paper Capacity	Max. 100 sheets (80 g/m <sup>2</sup> )	
Productivity (A4 Crosswise)	Simplex	Copy (Colour/B&W): 55 opm (600 dpi) Scan (Colour/B&W): 80 opm (300 dpi)
	Duplex	Copy (Colour/B&W): 26 opm (600 dpi) Scan (Colour/B&W): 37 opm (300 dpi)
Power Requirements	Supplied from the MFP main body	
Max. Power Consumption	60 W or less	
Dimensions [W] × [D] × [H]	611.2 × 503.6 × 130 mm (24" × 19-3/4" × 5")	
Weight	Anrox. 9 kg (19-3/4 lb)	