

bizhub 368e/308e

MONOCHROME MID-VOLUME MULTIFUNCTION PRINTERS

SYSTEM OVERVIEW

System memory	4 GB (when UK-211 is installed)
System hard disk	250 GB Standard
Interface	10-BASE-T / 100-BASE-TX / 1000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), FTP, SMB v2, SMTP, WebDAV
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Document feeder (optional)	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163gsm Reversing automatic document feeder or dual scan document feeder available
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes Banner paper max.: 11.75" x 47.25"
Printable paper weight	52–300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52–256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52–256 gsm
PC-115 Paper feed cabinet (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52–256 gsm
PC-215 Paper feed cabinet (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52–256 gsm
Large capacity tray PC-415 (optional)	2,500 sheets / 8.5" x 11" / 52–256 gsm
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52–256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50–300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52–256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,200 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	308e: 150,000 pages/month ¹ 368e: 175,000 pages/month ¹
Toner lifetime	25,000 pages
Imaging unit lifetime	308e: 265,000 pages / 600,000 pages (Drum/Developer) 368e: 270,000 pages / 600,000 pages (Drum/Developer)
Power consumption	120 V / 60 Hz, less than 1.5 kW (system)
System dimensions	24.2" x 27" x 38" (W x D x H)
System weight	Approx. 168 lbs

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32 / x64): 7 / 8.1 / 10 Windows Server (x32 / x64): 2008 / 2008 R2 ² / 2012 ² / 2016 ² Macintosh OS X 10.7 or later Linux / Unix / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri HD Polymerized Toner
Print speed (8.5" x 11")	308e: Up to 30 ppm (portrait) 368e: Up to 36 ppm (portrait)
Print speed (11" x 17")	308e: Up to 15 ppm (portrait) 368e: Up to 18 ppm (portrait)
Autoduplex speed (8.5" x 11")	308e: Up to 30 ppm (portrait) 368e: Up to 36 ppm (portrait)

COPIER SPECIFICATIONS (CONT.)

1st copy out time	308e: 4.8 seconds 368e: 4.5 seconds
Warm-up time	Approx. 20 seconds ³
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1–9,999
Original format	Up to 11" x 17"
Magnification	25–400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

SCANNER SPECIFICATIONS

Scan speed	B&W / Color: up to 160 opm with optional DF-704
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

FAX SPECIFICATIONS

Fax	Super G3 (optional)
Transmission	Analog, Internet Fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB, up to 400 job programs

USER BOX SPECIFICATIONS

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public Personal (with password or authentication) Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, and sending Email/FTP/SMB/fax, copy box-to-box

SYSTEM FEATURES

Security	ISO 15408 EAL ⁴ / IEEE 2600.1 ⁴ / IP filtering and port blocking / SSL2, SSL3 and TLS1.0 network communication / IPsec support / IEEE 802.1x support / FIPS 140-2 / User authentication / Authentication log / Secure print / Hard disk overwrite (8 standard types) / Hard disk data encryption (AES 128) / Memory data auto deletion / Confidential fax receipt / Print user data encryption / Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts Active Directory support (user name + password + email + SMB folder) User function access definition Optional Biometric authentication (finger vein scanner) Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

² Supports x64 only.

³ Warm-up time may vary depending on the operating environment and usage.

⁴ Certification pending.